

Dough divider Parta U

Universal dough divider

Specification

A unique dough divider, suitable for all kinds of dough. The use of the latest technical constructions, combined with many years of experience in the production of thousands of reliable dough dividers, results in an extremely accurate, universal machine with a proven long life time.

Advantages

- Suitable for all kinds of dough
- Gentle dough treatment
- Wide weight range : 110-2800 gr.
- Maximum adaption to mixer capacity
- Easy and quick cleaning
- Various lay outs possible
- User friendly
- Maximum safety
- Dough pieces are transported to rounder in a perfect way
- Modern design
- Maximum adaption to individual wishes



Illustration: Parta U

Basic execution Parta U :

- Cover plates in stainless steel
- Dividing unit in ni-resist
- Hingeable hopper in stainless steel, with safety ring, contents 120 L.
- Side-discharge conveyor, length 725 mm (Parta U 2001) and 1275 mm (Parta U 2002, U 2012 + U 2003) outside the machine, left hand or right hand
- Fixed capacity 925 pcs/h. (Parta U 2001), 1850 pcs/h. (Parta U 2002 + U 2012) and 2775 pcs/h. (Parta U 2003). Other fixed capacities on request.
- Automatic lubrication system



Parta U

Technical details

Type	Weight range	Capacity (fixed)	Variable (*)
- Type 2001	300 - 2800 gr.	925 or 1050 pcs/h.	615 - 1420 pcs/h.
- Type 2002	110 - 1250 gr.	1850 or 2100 pcs/h.	1230 - 2840 pcs/h.
- Type 2012	300 - 2800 gr./110 - 1250 gr.	925 or 1850 pcs/h./1050 - 2100 pcs/h.	615 - 1420 pcs/h./1230 - 2840 pcs/h.
- Type 2003	110 - 660 gr.	2775 or 3150 pcs/h.	1848 - 4224 pcs/h.

Dimensions Parta U

- Length 2470 mm. max.
- Width 1082 mm. max.
- Height 1839 mm. max.

Weight

- Net 620 Kg.
- Gross 820 Kg.

Connecting load

- 230/400 V, 50 Hz + earth
- 1,6 KVA

Options Parta U

- Discharge roller with scraper and brake motor
- Dough hopper hingeable, with safety ring. Capacity 170 l, H=1712 mm
- Dough hopper hingeable, with safety ring. Capacity 210 l, H=1782 mm
- Dough hopper hingeable, with safety ring. Capacity 245 l, H=1837 mm
- Hopper teflonized
- Oiling on hopper
- Belt oiling
- Position stop for easy cleaning
- Digital capacity display
- Variable capacity by means of frequency inverter with digital display
- Two mechanical flour dusters
- Mechanical pieces counter
- Oil shortage detection
- Electronical preferential counter
- Height machine increased by 100 mm, H=1712 mm

